



Dübellochbohrer (HW) Standard

Schaft mit Spannfläche und Einstellschraube.

Dowel Drill Bits (TCT) Standard

Shank with clamping flat and adjustment screw.

Ø D (mm)	Art. Nr.		€/ Stück		€/ piece
	rechts/right	links/left	1-19	> 20	> 50

L = 57,5mm; L1 = 27mm; S = 10 x 27mm

5	4.05.57.01	4.05.57.11	15,70	14,90	14,10
6	4.06.57.01	4.06.57.11	16,10	15,30	14,50
7	4.07.57.01	4.07.57.11	18,10	17,30	16,30
8	4.08.57.01	4.08.57.11	17,30	16,40	15,60
9	4.09.57.01	4.09.57.11	20,60	19,50	18,60
10	4.10.57.01	4.10.57.11	19,40	18,50	17,50
11	4.11.57.01	4.11.57.11	23,30	22,10	21,00
12	4.12.57.01	4.12.57.11	23,80	22,60	21,40



Art. 4.05.70.01

Art. 4.05.70.11
Maßstab 1:1
Full size

L = 70mm; L1 = 35mm; S = 10 x 27mm

5	4.05.70.01	4.05.70.11	17,00	16,10	15,20
6	4.06.70.01	4.06.70.11	17,60	16,70	15,90
7	4.07.70.01	4.07.70.11	18,10	17,30	16,30
8	4.08.70.01	4.08.70.11	18,30	17,40	16,40
9	4.09.70.01	4.09.70.11	21,30	20,20	19,10
10	4.10.70.01	4.10.70.11	20,60	19,50	18,60
12	4.12.70.01	4.12.70.11	24,50	23,30	22,00

L = 77mm; L1 = 44mm; S = 10 x 27mm

5	4.05.77.01	4.05.77.11	19,40	18,50	17,50
6	4.06.77.01	4.06.77.11	20,60	19,50	18,60
8	4.08.77.01	4.08.77.11	22,00	21,00	19,90
10	4.10.77.01	4.10.77.11	23,80	22,60	21,40
12	4.12.77.01	4.12.77.11	25,70	24,40	23,10

