

Durchgangsbohrer (HW) Standard
60° Dachformspitze; Schaft mit Spannfläche und Einstellschraube.



Through-Hole Drill Bits (TCT) Standard
60° v-point tip; shank with clamping flat and adjustment screw.

Ø D x L1 (mm)	Art. rechts/right	links/left	€/ Stück		€/ piece
			1-19	> 20	> 50

L = 57,5mm; S = 10 x 27mm

5 x 21	5.05.57.01	5.05.57.11	20,40	19,40	18,40
6 x 21	5.06.57.01	5.06.57.11	21,00	20,80	19,80
7 x 21	5.07.57.01	5.07.57.11	22,10	21,10	20,00
8 x 21	5.08.57.01	5.08.57.11	21,80	20,70	19,70
9 x 20	5.09.57.01	5.09.57.11	25,00	23,70	22,50
10 x 20	5.10.57.01	5.10.57.11	24,70	23,50	22,20
12 x 20	5.12.57.01	5.12.57.11	29,20	27,80	26,20

L = 70mm; S = 10 x 27mm

5 x 32	5.05.70.01	5.05.70.11	21,30	20,20	19,10
6 x 32	5.06.70.01	5.06.70.11	21,90	20,80	19,80
7 x 32	5.07.70.01	5.07.70.11	26,00	24,70	23,40
8 x 32	5.08.70.01	5.08.70.11	22,70	21,60	20,40
9 x 32	5.09.70.01	5.09.70.11	25,90	24,60	23,30
10 x 32	5.10.70.01	5.10.70.11	25,50	24,20	22,90
12 x 32	5.12.70.01	5.12.70.11	30,10	28,60	27,10

L = 77mm; S = 10 x 27mm

5 x 37	5.05.77.01	5.05.77.11	24,50	23,30	22,00
6 x 39	5.06.77.01	5.06.77.11	25,50	24,20	22,90
7 x 39	5.07.77.01	5.07.77.11	28,30	26,90	25,50
8 x 37	5.08.77.01	5.08.77.11	25,10	23,80	22,60
9 x 37	5.09.77.01	5.09.77.11	38,70	36,70	34,80
10 x 36	5.10.77.01	5.10.77.11	28,70	27,30	25,80
12 x 36	5.12.77.01	5.12.77.11	33,30	31,60	29,90



Art. 5.05.77.01

Art. 5.05.77.11
Maßstab 1:1
Full size

Diverse Längeneinstellschrauben.
Siehe Seite 44.
Various length - adjustment screws.
See page 44.